

Pallet roller conveyors

INQUIRY-FORM



Project: _____ **Zip code delivery:** _____

Date: _____ **Freight** yes no
Assembly yes no

Assembly environment: deep-freeze enviroment -5° - -35° dry hall area +5° - +35°
 depp-freeze room +5° uncovered outdoor activities -20° - + 35°

FIFO LIFO shelf assembly ground mounted *Required fields

1.)Pallet *


Pallets

Typ:	Euro	Indu	Chep	Special	overcharge:	length: _____mm
Length:	1.200 mm	1.200 mm	_____	_____		width: _____mm
Width:	800 mm	1.000 mm	_____	_____	Number pallet place per conveyor:	_____ pieces _____
Height:	_____	_____	_____	_____	Way to transportation:	along _____ crossway _____
Weight:	_____	_____	_____	_____	Slope:	2,5 %
min.	_____	_____	_____	_____		
max.	_____	_____	_____	_____		

2.) Storage *

Forklift

- front loader/reach truck mast tiltable mast not tiltable
- stocker crane with telescopic lifting fork mast tiltable mast not tiltable
- stocker crane with rolling able tiltable not tiltable
- electro-stackers
- others _____



3.) Outsourcing *

Forklift

- front loader/reach truck mast tiltable mast not tiltable
- stocker crane with telescopic lifting fork mast tiltable mast not tiltable
- electro-stackers
- elevating-platform / electro pallet truck with buffers without buffers
 with ramps without ramps
- empty pallets removal-hand
- others _____



4.) Execution

Equipment

- water / dust protection
- task element 2 - divided
- task element 3 - divided
- entry guide heavy Version
 low Version
- order picking module 2 - divided
- order picking module 3 - divided
- flow conveyors 2 divided with end stop
- flow conveyors 3 divided with end stop with buffers
 with ramps
- roller protection
- 1. roller reinforced
- springy mounted brake rollers
- middle seperating divice
- Separating apparatus:**
- normal with hand release mechanics
- reinforced with foot release mechanics
- special design
- seesaw
- push back blocking unit
- end stop
- concrete trusses for 3.800 mm rest of the web on support
- ball bearing side guide rollers
- lateral guide profile
- hinged member with / without gas spring
- clamping hook